

# Comant CI 120-5

## Power Combiner

**COBHAM**

### 2008 Data Sheet

The most important thing we build is trust

#### CI 120-5 Power Combiner

Two input - two output Power Combiner is standard equipment with Comant's CI 120-200G/S-L as supplied to Cessna. The CI 120-5 allows for 2 separate coaxial cable runs to the avionics installation for NAV1 and NAV2 receivers.

#### Applications

Internal mount.

#### Frequencies Covered

108-118 MHz & 329-335 MHz

#### Specifications

##### Electrical

Frequency	108-118 MHz	329-335 MHz
VSWR	1.5:1 Maximum	1.5:1 Max.
Power Split	6 dB	6 dB
Isolation (btwn Ports)	20 dB	20 dB
Insertion Loss	1.5 dB Max.	1.5 dB Max.
Amplitude Balance	+-.5 dB	+-.5 dB
Impedence	50 Ohms	50 Ohms
Phase (btwn Ports)	+180° /+5	+180° /+5

##### Mechanical

Weight	0.25 lbs
Height	0.88 inches max.
Construction	Die Cast Aluminum
Finish	Aluminum
Connector	BNC (female)

##### Environmental

N/A	Internal Mount
-----	----------------

##### Federal Specifications

FAA TSO	C34e, C36e, C40c
RTCA Environmental	DO-160D



WARNING: Use factory supplied drawings and specifications for installation. Refer to FAA AC 43.13-2B for installation guidelines.

For further information please contact:

Cobham SATCOM Airborne Systems  
577 Burning Tree Road  
Fullerton, California 92833 USA  
Tel: (01) 714-870-2420  
Fax: (01) 714-870-5133  
Email: comant@cobham.com