Comant CI 120 G/S

VOR/LOC/GS

COBHAM

2008 Data Sheet

The most important thing we build is trust

CI 120-G/S

VOR/GS navigation antenna set provides optimum VOR performance when used for area navigation. Antenna system qualified for use on single engine, twin, jet, and helicopter aircraft.

Provides glideslope reception capability. Complete set includes a pair (2) of blades, each with single BNC connector output, two coax interconnect cables and a signal combiner output providing for a single cable run to the avionics installation.

Applications

Most aircraft up to and including business jets. Consult your FBO or installation shop for best application information.

Frequencies Covered

108-118 MHz (VOR/LOC), 329-335 MHz (GS)

Specifications Electrical

Cork

Electrical	
Frequency	108-118 MHz (VOR/LOC) 329-335 MHz (GS)
VSWR	6.0:1 108-118 MHz 5.0:1 329-335 MHz
Polarization	Horizontal
Radiation Pattern	Omni Directional
Impedance RF	50 Ohms Nominal
Power RF	Receive Only
Mechanical	
Weight	1.4 lb Per Blade
Height	6.0 Inches Maximum
Finish	Polyurethane Enamel
Connector	BNC / Single Output Combiner
Environmental	
Temperature	-55 C to +85 C
Altitude	50,000 ft
Airspeed	600 Knots TAS @ 25,000 ft.
Federal Specifications	
FAA TSO	C34e, C36e, C40c
RTCA MOPS	DO-192, DO-195, DO-196
RTCA Environmental	DO-160D
Gasket	

B12014



For further information please contact:

Cobham SATCOM Airborne Systems 577 Burning Tree Road Fullerton, California 92833 USA Tel: (01) 714-870-2420

Fax: (01) 714-870-2420 Fax: (01) 714-870-5133 Email: comant@cobham.com