

Comant CI 139

VHF Communication

COBHAM

2008 Data Sheet

The most important thing we build is trust

CI 139 VHF Communication

Piper compatible mounting version of the CI 119 with respect to the mounting hole pattern and RF connector location.

The CI 139 has been re-tested and upgraded to the new RTCA DO-160D environmental requirements and offers the 118 to 137 MHz frequency associated with DO-186A.

Applications

Single and twin engine piston aircraft for applications of this antenna design. Consult your FBO or installation shop for best application information.

Frequencies Covered

118-137 MHz

Specifications

Electrical

Frequency	118-137
VSWR	2.9:1 Maximum
Polarization	Vertical
Radiation Pattern	Omnidirectional
Impedance RF	50 Ohms
Power RF	25 Watts

Mechanical

Weight	1.25 lbs Max.
Height	13.00 inches Max.
Material	Valox 420
Finish	Polyurethane Enamel
Connector	BNC (female)

Environmental

Temperature	-55 to +85 Celcius
Altitude	50,000 ft.
Airspeed	350 KTAS @ 25,000 ft.

Federal Specifications

FAA TSO	C37d, C38d
RTCA Environmental	DO-160D

Gasket

C13904	Cork Neoprene
--------	---------------



WARNING: Use factory supplied drawings and specifications for installation. Refer to FAA AC 43.13-2B for installation guidelines.

For further information please contact:

Cobham SATCOM Airborne Systems
577 Burning Tree Road
Fullerton, California 92833 USA
Tel: (01) 714-870-2420
Fax: (01) 714-870-5133
Email: comant@cobham.com