

Comant CI 2680-200

ComDat VHF/GPS

COBHAM

2008 Data Sheet

The most important thing we build is trust

CI-2680-200 ComDat VHF/GPS

Comant's PCS/Timing CI 2680-1 is designed for use with Aircell Broadband Systems (ABS).

Contact Aircell for price, availability and installation guidelines.

Applications

Single and twin engine piston aircraft for applications of this antenna design. Some light turbine and light jets. Consult your FBO or installation shop for best application information.

Frequencies Covered

VHF 118-137 MHz

GPS 1575.42 MHz / 26.5 dB Gain

Specifications

VHF Specifications

Frequency	118-137 MHz
VSWR	2.9:1 Maximum
Polarization	Vertical
Radiation Pattern	Omni Directional
Impedance	50 Ohms
Power Rating	50 Watts

GPS Preamplifier Specs

Frequency	1575.42 +/-3 MHz
VSWR	1.5:1 Max.
Polarization	RHCP
Radiation Pattern	Hemispherical
Impedance	50 Ohms
Gain	26.5 - 31.5 dB
DC Voltage	4 - 24 Vdc
DC Curr. Min/Max	25mA / 40mA
Noise	3.8 dB Max

Mechanical / Environmental

Weight	1.25 lbs Maximum
RTCA Env. / TSO	DO 160D / C37d, C38d, C144
Connectors	VHF - BNC / GPS - TNC



WARNING: Use factory supplied drawings and specifications for installation. Refer to FAA AC 43.13-2B for installation guidelines.

For further information please contact:

Cobham SATCOM Airborne Systems
577 Burning Tree Road
Fullerton, California 92833 USA
Tel: (01) 714-870-2420
Fax: (01) 714-870-5133
Email: comant@cobham.com