

Comant CI 273

UHF Radiotelephone



The most important thing we build is trust

CI 273 Radiotelephone

Identical to CI 271 except its electrical performance is specified over the frequency range of 403-512 MHz in various band segments with VSWR limits shown. Stub antenna designed to withstand the harsh environments associated with the underside of an aircraft. Antenna radiator is mechanically captivated and is sealed against leakage. All exposed metal surfaces are nickel-plated for corrosion resistance and long service. CI 273 mounts through a single 0.60" hole. BNC connector is standard.

Applications

Single engine piston aircraft for applications of this antenna design. Consult your FBO or installation shop for best application information.

Frequencies Covered

403-512 MHz

Specifications

Electrical	
Frequency	403-512 MHz
VSWR	3.0:1 @ 403 to 512 MHz
	3.0:1 @ 403 to 430 MHz
	2.0:1 @ 430 to 470 MHz
	3.0:1 @ 470 to 512 MHz
Polarization	Vertical
Radiation Pattern	Equivalent to 1/4 wave Stub
Impedance	50 Ohms
RF Power	50 Watts Average
Mechanical	
Weight	0.18 lbs
Height	7.0 inches Maximum
Material	Nickel plated brass
Finish	Tin-nickel alloy
Connector	BNC (female)
Federal Specifications	
FAA TSO	N/A



WARNING: Use factory supplied drawings and specifications for installation. Refer to FAA AC 43.13-2B for installation guidelines.

Order at:
Tel: 714-870-2420 Fax: 714-870-6294
Email: comantorders@cobham.com