Product Summary



RangePRO Model L-GM5 Laser Rangefinder Module





"Advanced digital rangefinding technology: precise, compact, robust."

Laser rangefinder -**G**eneral Module to 5Hz rep. rate

Dimens	ions ****			
length	312.6 mm;			
width	237.1 mm;			
height	143 mm;			
mass	5.6 kg.			
**** including scope				

Transmitter		
laser type	diode pumped Nd:YAG/OF	PO;
wavelength	1,570 nm;	
output	< 8mJ;	
ranging rate	5Hz typical, up to 10Hz (50% duty cycle	:).

Detector

Power

InGaAs with time variant gain.

Range Determination

Signals from the detector are digitally sampled and examined to determine all potential real target returns. An adaptive range threshold compensates for changing noise levels, maximising system capability under varying conditions.

12 to 32Vdc input.

Comms

RS-422 19,200 Baud.

V-block type.

Reference Laser

laser type	laser diode;		
wavelength	635 nm;		
output	< 0.5mW.		

Options

vertical configuration, mounting 3-point mount;

detector APD.

Suitability

OEM module for integration into thermal sensing, surveillance, tracking & weapons stations;

for ground mobile and fixed installation applications;

designed to withstand vibration, shock, and extended temperature operation, EM shielded.

Rangefindii	ng		
read-out lim	its	min.	100;
(factory sele	ctable)	max.	30,000.
perform-	small cra	ft (2.3x2.3m)	
ance *	large cra	ft (20x20m) *	> 20,000.

* Standard Clear atmosphere; Extinction Coefficient 0.0448 @ 1,570nm (Modtran 3 V1.5; tropical atmosphere, maritime aerosols, Jan.); sea level visibility = 23.5km.

Sealing

Hermetic.

Laser Safety

Class 1M.

AS/NZS 2211.1, IEC825-1.



A Division of Laserdyne Pty Ltd A.C.N. 053 743 132

P.O. Box 6541 GCMC Bundall Queensland 9726 Australia

17 Production Ave Molendinar Queensland 4214 Australia

Tel: (07) 5594 9772 Fax: (07) 5594 9981 Int'l Fax: 61 7 5594 9981

Int'l Tel: 61 7 5594 9772

email: laserdyne@laserdyne.com.au website: www.laserdyne.com.au

The information contained herein is proprietary to Laserdyne Pty Ltd. No part of this work may be reproduced or copied in any way without prior written permission of Laserdyne Pty Ltd. Note: specifications herein are subject to change without notice.

Copyright. All Rights Reserved. Laserdyne Pty Ltd

File: SD-RP-S-1465-B 1 Author(s): NG,JK,MW,TW Authorised: TW Rev. Date: 12.7.13 Page 1

Target albedo = 0.3 @ 1,570nm.