

# 500VA STATIC INVERTER

### MD50 SERIES

MANUFACTURED BY MID-CONTINENT INSTRUMENTS



- Supplies power for various cabin accessories such as laptops, cell phones and iPods°
- Compact design 30% smaller than competing products
- Lightweight
- Remote On/Off feature
- 500VA output power
- **●** 85-90% efficiency
- Input Voltage: 24-32 VDC
- Input Current: 20A at 28 VDC input
- Output Voltage: 115 VAC
- Frequency: 60 Hz ± 1%
- Single phase, true sine wave output
- Overload and short circuit protection up to 150% of rated load
- Rated from -65 F°to +160°F (-55°C to +71°C)
- FAA TSO C73 certification and RTCA D0-160F qualification pending
- Designed and built in Wichita, Kansas, USA
- One year limited warranty

Kansas 9400 E. 34th Street North Wichita, KS 67226 USA Tel 800-821-1212 316-630-0101 Fax 316-630-0723 mci@mcico.com



WWW.MCICO.COM WWW.LIFESAVERGYRO.COM California 16320 Stagg Street Van Nuys, CA 91406 USA Tel 800-345-7599 818-786-0300 Fax 818-786-2734 mcw@mcico.com

## **500VA STATIC INVERTER**

### MD50 SERIES

MANUFACTURED BY MID-CONTINENT INSTRUMENTS

#### **SPECIFICATIONS**

Input Voltage: 24-32 VDC

Input Current: 17 to 23A

Output Power: 500VA

Output Voltage: 115 VAC

Output Waveform: Single phase, true sine wave

Output Frequency: 60 Hz ± 1%

Efficiency: 85-90%

Weight: 3.8 lbs.

Altitude: 55,000 ft.

Humidity: Tested to greater than 95%

for 10 days, temperature was cycled between 75°F to 160°F

Temperature:  $-65^{\circ}F$  to  $+160^{\circ}F$  ( $-55^{\circ}C$  to  $+71^{\circ}C$ )

Protection: Input transient, overload and short circuit protection

(up to 150% of rated load without damage)

Connector: MS3102A-18-9P

Mating Connector: MS3106A-18-9S

Case: Anodized aluminum, blue

Certification: FAA TSO C73 and RTCA D0-160F pending







